Declaration of Performance

No. DOP/SL70-210901

1	Product type	SL70 steel cavity lintel							
2	Product type number	BA0							
3	Intended use	In cavity walls							
4	Manufacturer	Stressline Limited Foxbank Industrial Estate Stoney Stanton Leicestershire LE9 4LX United Kingdom							
5	Authorised representative	Not applicable							
6	System of assessment of performance	System 3							
7	Reference harmonised standard	BS 845-2:2013 Assessment: Lucideon (NB1289) Reference: 133162 (QT-27317/3/SL)/Ref. 2							
8	European Technical Assessment	Not applicable							
9	Declared performance								
9.1	Load bearing capacity (kN)	Lintel Length (mm)							
		600-1200	1350-1500	1650-1800	1950-2100	2250-2400	2550-3000	3150-3900	4050-4200	4350-4800
	Load ratio 1:1/3:1	16	17	22	23	24	28	28	28	28
	Load ratio 19:1	12	13	17	18	19	22	22	22	22
9.2	Deflection under load	≤ Effective span/325 at safe working load							
9.2	Water absorption	Zero							
9.3	Direct airborne sound insulation (kg/m^2)	67.4	61.9	57.5	56.4	54.2	50.0	74.7	68.4	81.3
9.4	Thermal resistance	Steel: 50 W/(m.K) Polystyrene: 0.035 W/(m.K)							
9.5	Resistance to fire	NPD							
9.6	Durability of performance (corrosion)	Material: Z600 galvanised steel							
9.7	Durability of performance (freeze/thaw)	Resistant							
9.8	Dangerous substances	Not applicable							

10 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Stoney Stanton, September 2021

Chris Fox
Managing Director

UK CA

Stressline Limited, Foxbank Industrial Estate, Leicestershire, LE9 4LX

21

Lucideon (NB1289) Reference: 133162 (QT-27317/3/SL)/Ref. 2

BS 845-2

SL70 steel cavity lintel,
intended to be used in cavity walls

Load bearing capacity	Lintel Length (mm)								
	600-1200	1350-1500	1650-1800	1950-2100	2250-2400	2550-3000	3150-3900	4050-4200	4350-4800
Load ratio 1:1/3:1	16	17	22	23	24	28	28	28	28
Load ratio 19:1	12	13	17	18	19	22	22	22	22
Deflection under load	≤ Effective span/325 at safe working load								
Water absorption	Zero								
Direct airborne sound insulation (kg/m^2)	67.4	61.9	57.5	56.4	54.2	50.0	74.7	68.4	81.3
Thermal resistance	Steel: 50 W/(m.K) Polystyrene: 0.035 W/(m.K)								
Resistance to fire	NPD								
Durability of performance (corrosion)	Material: Z600 galvanised steel								
Durability of performance (freeze/thaw)	Resistant								
Dangerous substances	Not applicable								

See also Declaration of Performance DOP/SL70-210901